



### Tabla de Aplicación OKO México RTG

Camiones pesados de más de 5 toneladas; remolques, camiones de carga, transporte turístico, autobuses y vehículos militares de carga.

**Velocidad máxima:** 130 km/hr

**Capacidad de sellado:** 8 mm

Neumático	Rin	Litros
<b>Rin 15 "</b>		
12.00 - 15	15	1.850
<b>Rin 16 "</b>		
6.50 R16 LT	16	0.750
7.00 - 16	16	0.900
225/75 - 16	16	1.100
8.25 - 16	16	1.150
8.35 - 16	16	1.200
235/85 - 16	16	1.250
245/75 - 16	16	1.250
9.00 - 16	16	1.300
255/85 - 16	16	1.400
265/75 - 16	16	1.400
245 - 16	16	1.450
285/75 - 16	16	1.500
10.50 - 16	16	1.650
11.00 - 16	16	1.750
14.00 - 16	16	2.400
<b>Rin 16.5 "</b>		
8.00 - 16.5	16.5	1.150
8.75 - 16.5	16.5	1.300
9.50 - 16.5	16.5	1.450
10.00 - 16.5	16.5	1.600
12.00 - 16.5	16.5	2.100
<b>Rin 17 "</b>		
7.00 - 17	17	1.000
7.50 - 17	17	1.100
8.00 - 17	17	1.200
8.25 - 17	17	1.250
8.75 - 17	17	1.350
9.50 - 17	17	1.500
10.00 - 17	17	1.650
12.00 - 17	17	2.100
<b>Rin 17.5 "</b>		
7.00 - 17.5	17.5	1.000
205/75 - 17.5	17.5	1.100
215/75 - 17.5	17.5	1.150

Neumático	Rin	Litros
<b>Rin 17.5 "</b>		
8.00 - 17.5	17.5	1.250
225/75 - 17.5	17.5	1.250
235/75 - 17.5	17.5	1.300
8.50 - 17.5	17.5	1.350
9.00 - 17.5	17.5	1.450
9.50 - 17.5	17.5	1.550
10.00 - 17.5	17.5	1.700
11.00 - 17.5	17.5	1.900
14.00 - 17.5	17.5	2.600
<b>Rin 18 "</b>		
7.00 - 18	18	1.050
7.50 - 18	18	1.150
9.00 - 18	18	1.500
10.00 - 18	18	1.750
10.50 - 18	18	1.850
12.50 - 18	18	2.300
12.50 - 18	18	2.300
14.00 - 18	18	2.700
<b>Rin 19.5 "</b>		
7.00 - 19.5	19.5	1.150
8.00R19.5	19.5	1.250
245/70 - 19.5	19.5	1.500
255/70 - 19.5	19.5	1.600
9.00 - 19.5	19.5	1.650
265/70 - 19.5	19.5	1.650
9.50 - 19.5	19.5	1.750
285/70 - 19.5	19.5	1.800
10.00 - 19.5	19.5	1.850
305/70 - 19.5	19.5	1.950
15.00 - 19.5	19.5	3.150
16.5R19.5	19.5	3.150
16.00 - 19.5	19.5	3.450
19.5R19.5	19.5	3.750
18.00 - 19.5	19.5	4.000
19.50 - 19.5	19.5	4.600



### Tabla de Aplicación OKO México RTG

Camiones pesados de más de 5 toneladas; remolques, camiones de carga, transporte turístico, autobuses y vehículos militares de carga.

**Velocidad máxima:** 130 km/hr

**Capacidad de sellado:** 8 mm

Neumático	Rin	Litros
<b>Rin 20"</b>		
120.00/80 -20	20	0.650
6.50 - 20	20	1.100
7.00 - 20	20	1.200
7.50 - 20	20	1.300
8.25 - 20	20	1.500
9.00 - 20	20	1.700
10.00 - 20	20	1.900
10.50 - 20	20	2.100
11.00 - 20	20	2.200
12.00 - 20	20	2.400
13.00/80 - 20	20	2.400
13.00R20	20	2.400
12.50 - 20	20	2.600
14.00/80 - 20	20	2.600
14.00R20	20	2.600
13.00 - 20	20	2.700
365/80 - 20	20	2.700
15.50/80 - 20	20	2.900
405/75 - 20	20	2.900
14.00 - 20	20	3.000
14.50 - 20	20	3.150
14.75 - 20	20	3.150
15.00 - 20	20	3.300
16.00 - 20	20	3.600
<b>Rin 20.5 "</b>		
525/65 - 20.5	20.5	3.750
615/65 - 20.5	20.5	4.600
<b>Rin 21 "</b>		
12.00 - 21	21	2.500
14.00R21	21	2.700
<b>Rin 22 "</b>		
9.00 - 22	22	1.850

Neumático	Rin	Litros
<b>Rin 22 "</b>		
10.00R22	22	1.900
11.00 - 22	22	2.400
<b>Rin 22.5 "</b>		
235/80 - 22.5	22.5	1.750
245/75R22.5	22.5	1.800
255/70 - 22.5	22.5	1.850
9.00 - 22.5	22.5	1.900
255/80 - 22.5	22.5	1.950
265/75R22.5	22.5	1.950
275/70 - 22.5	22.5	2.000
11.00/70 -22.5	22.5	2.100
275/80 - 22.5	22.5	2.100
10.00 - 22.5	22.5	2.200
295/75R22.5	22.5	2.200
11.00 - 22.5	22.5	2.200
12.00/70 -22.5	22.5	2.300
295/80 - 22.5	22.5	2.300
315/70 - 22.5	22.5	2.300
315/75 - 22.5	22.5	2.400
315/80 - 22.5	22.5	2.500
12.00 - 22.5	22.5	2.700
345/75 - 22.5	22.5	2.700
12.50 - 22.5	22.5	2.800
365/70 - 22.5	22.5	2.800
12.75 - 22.5	22.5	2.900
13.00 - 22.5	22.5	3.000
385/80 - 22.5	22.5	3.150
425/65 - 22.5	22.5	3.150
445/65 - 22.5	22.5	3.300
16.5R22.5	22.5	3.450
15.00 - 22.5	22.5	3.600
18.00 - 22.5	22.5	4.600



### Tabla de Aplicación OKO México RTG

Camiones pesados de más de 5 toneladas; remolques, camiones de carga, transporte turístico, autobuses y vehículos militares de carga.

**Velocidad máxima:** 130 km/hr

**Capacidad de sellado:** 8 mm

Neumático	Rin	Litros
<b>Rin 24"</b>		
9.00 - 24	24	2.000
10.00 - 24	24	2.300
11.00R 24	24	2.300
10.00 - 24	24	2.300
12.00R 24	24	2.600
13.00R 24	24	2.800
14.00R 24	24	3.150
14.00/80 - 24	24	3.150
405/70 - 24	24	3.300
14.00 - 24	24	3.450
<b>Rin 24.5"</b>		
275/80 - 24.5	24.5	2.300
285/75R24.5	24.5	2.400
295/80 - 24.5	24.5	2.500
305/75 - 24.5	24.5	2.500
<b>11.00 - 24.5</b>	<b>24.5</b>	<b>2.600</b>
315/75 - 24.5	24.5	2.600
12.00 - 24.5	24.5	2.900
13.50 - 24.5	24.5	3.450
<b>Rin 25"</b>		
11.00 - 25	25	2.700
12.00 - 25	25	3.000
14.00R 25	25	3.150